FR 795 SCC OE DMT | Over Extension Progressive Action Drawer Slide



Specifications

- side mount
- 18.0 mm / 0.71 in
- dynamic up to 60 kg / 132 lbs
- solid synthetic rollers
- stainless steel 1.4509 / 441
- -25 °C to +80 °C
  -13 °F to +176 °F

Characteristics

- high lateral stability
- ideal running characteristic and smoothness of running through integrated progressive action
- integrated safety clip
- dual-sided captive profile
- synthetic stop
- self-closing
- available as heat-resistant version up to +110 °C (+230 °F)
- Easy Close Device (ECD) can be ordered optionally, from length 350 mm (13.78 in)

Mounting Type

- cabinet and drawer profiles with Standard Mounting Tabs (DMT) and safety nose
- tool-less quick assembly of cabinet and drawer profiles

Dimensions



Length		Extension		Weight		Item No.	Item No.
				per set		PU 1	PU 2
mm	inch	mm	inch	kg	lbs		
300	11.81	335	13.19	1.38	3.04	* 1024281002	* 1024281602
350	13.78	385	15.16	1.46	3.22	▸ 1024421002	▸ 1024421602
400	15.75	460	18.11	1.69	3.73	* 1024571002	* 1024571602
450	17.72	510	20.08	1.93	4.26	* 1024731002	▸ 1024731602
500	19.69	560	22.05	2.16	4.76	* 1024871002	▸ 1024871602
550	21.65	610	24.02	2.40	5.28	* 1025051002	▸ 1025051602
600	23.62	660	25.98	2.64	5.82	* 1025191002	* 1025191602
650	25.59	710	27.95	2.87	6.33	* 1025331002	▸ 1025331602
700	27.56	760	29.92	3.11	6.86	* 1028281002	* 1028281602
750	29.53	810	31.89	3.37	7.43	* 1028411002	* 1028411602

Packing Unit

▸ in stock | * on request

PU 1 – Sets assembled per Box, all Lengths: 5
PU 2 – 50 Sets, all 6 profiles individually packaged, 10 boxes
(4 x 25 cabinet profiles LEFT/RIGHT, 4 x 25 middle profiles LEFT/RIGHT, 2 x 50 drawer profiles LEFT/RIGHT)

Fulterer